

| | | Systemgewicht [Kg] | | | | | | |
|----------------|-----|--------------------|-------|------|-------|------|-------|-------|
| | | Breite [cm] | | | | | | |
| | | 200 | 250 | 300 | 350 | 400 | 450 | 500 |
| Ausladung [cm] | 200 | 54.8 | 61.15 | 67.5 | 73.85 | 80.2 | 86.55 | 92.2 |
| | 250 | 55.9 | 62.25 | 68.6 | 74.95 | 81.3 | 87.65 | 94 |
| | 300 | 57 | 63.35 | 69.7 | 76.05 | 82.4 | 88.75 | 95.1 |
| | 350 | 60.1 | 66.45 | 72.8 | 79.15 | 85.5 | 91.85 | 98.2 |
| | 400 | 61.2 | 67.55 | 73.9 | 80.25 | 86.6 | 92.95 | 99.3 |
| | 450 | 62.3 | 68.65 | 75 | 81.35 | 87.7 | 94.05 | 100.4 |
| | 500 | 63.4 | 69.75 | 76.1 | 82.45 | 88.8 | 95.15 | 101.5 |
| | 550 | 64.5 | 70.85 | 77.2 | 83.55 | 89.9 | 96.25 | 102.6 |
| | 600 | 65.6 | 71.95 | 78.3 | 84.65 | 91 | 97.35 | 103.7 |

| | | Anzahl der Führungsschienenhalter [Paar] | | | | | | |
|----------------|------|------------------------------------------|------|------|------|------|------|------|
| | | Breite [mm] | | | | | | |
| | | 2000 | 2500 | 3000 | 3500 | 4000 | 4500 | 5000 |
| Ausladung [mm] | 2000 | 2 | 2 | 2 | 2 | 2 | 2 | 2 |
| | 2500 | 2 | 2 | 2 | 2 | 2 | 2 | 2 |
| | 3000 | 2 | 2 | 2 | 2 | 2 | 2 | 2 |
| | 3500 | 3 | 3 | 3 | 3 | 3 | 3 | 3 |
| | 4000 | 3 | 3 | 3 | 3 | 3 | 3 | 3 |
| | 4500 | 4 | 4 | 4 | 4 | 4 | 4 | 4 |
| | 5000 | 4 | 4 | 4 | 4 | 4 | 4 | 4 |
| | 5500 | 4 | 4 | 4 | 4 | 4 | 4 | 4 |
| | 6000 | 4 | 4 | 4 | 4 | 4 | 4 | 4 |