

		Systemgewicht [kg]													
		Breite [cm]													
		125	150	175	200	225	250	275	300	325	350	375	400	425	450
Ausladung [cm]	150	25.10	27.98	30.86	33.73	36.61	39.49	42.37	45.24	48.12	51.00	53.88	56.75	59.63	62.51
	175	25.77	28.64	31.52	34.40	37.28	40.15	43.03	45.91	48.79	51.66	54.54	57.42	60.30	63.17
	200	26.43	29.31	32.19	35.06	37.94	40.82	43.70	46.57	49.45	52.33	55.21	58.08	60.96	63.84
	225	27.10	29.97	32.85	35.73	38.61	41.48	44.36	47.24	50.12	52.99	55.87	58.75	61.63	64.50
	250	27.76	30.64	33.52	36.39	39.27	42.15	45.03	47.90	50.78	53.66	56.54	59.41	62.29	65.17
	275	28.43	31.30	34.18	37.06	39.94	42.81	45.69	48.57	51.45	54.32	57.20	60.08	62.96	65.83
	300	29.09	31.97	34.85	37.72	40.60	43.48	46.36	49.23	52.11	54.99	57.87	60.74	63.62	66.50
	325	29.76	32.63	35.51	38.39	41.27	44.14	47.02	49.90	52.78	55.65	58.53	61.41	64.29	67.16
	350	30.42	33.30	36.18	39.05	41.93	44.81	47.69	50.56	53.44	56.32	59.20	62.07	64.95	67.83
	375				39.72	42.60	45.47	48.35	51.23	54.11	56.98	59.86	62.74	65.62	68.49
	400				40.38	43.26	46.14	49.02	51.89	54.77	57.65	60.53	63.40	66.28	69.16
	425				41.05	43.93	46.80	49.68	52.56	55.44	58.31	61.19			
	450				41.71	44.59	47.47	50.35	53.22	56.10	58.98				
	475				42.38	45.26	48.13	51.01	53.89	56.77					
500					45.92	48.80	51.68	54.55							

Bemerkungen: Systemgewichte können variieren +/- 10%

Anzahl Führungsschienenhalter [Paar]		
Ausladung [mm]	0+1500	2
Ausladung [mm]	1501+2500	3
Ausladung [mm]	2501+4000	4
Ausladung [mm]	4001+5000	5